

Matrox Odyssey eCL/XCL

Camera Interface Application Note

ADIMEC 4000m/D

April 16, 2008

*Basics about the
camera*

Camera Descriptions

- Effective resolution: 2048 × 2048 × 10-bit @ 16 fps.
- Camera Link BASE interface (Dual channel).
- Progressive scan.
- Internal sync.
- Internal or external exposure control.
- 40 MHz pixel clock rate.

Interface Mode

- Continuous
- Pseudo-continuous
- Asynchronous reset (Control mode)

Camera Interface Briefs

Mode 1: Continuous

- 2048 × 2048 × 10-bit @ 16 fps.
- Camera Link BASE interface (Dual channel).
- Progressive scan.
- Matrox Odyssey eCL/XCL receiving LDV, FDV, CLK and video signal from camera.
- DCF used: [4000mD2048x2048_10bit2TapCon.DCF](#)



Mode 2: Pseudo-continuous

- 2048 × 2048 × 10-bit.
- Camera Link BASE interface (Dual channel).
- Progressive scan.
- Matrox Odyssey eCL/XCL sending periodic EXPOSURE1 (CC1) signal to camera to initiate and control exposure time.
- Matrox Odyssey eCL/XCL receiving LDV, FDV, CLK and video signal from camera.

Continued

*Mode of operations as
per Matrox Imaging (in
parentheses as per
camera manufacturer)*

*Basics about the
interface modes*

Matrox Odyssey eCL/XCL

Camera Interface Application Note

ADIMEC 4000m/D


April 16, 2008

Basics about the
interface modes

Camera Interface Briefs (cont.)


Mode 2: Pseudo-continuous

- DCF used: [4000mD2048x2048_10bit2TapPcon.DCF](#)



Mode 3: Asynchronous reset

- 2048 × 2048 × 10-bit.
- Camera Link BASE interface (Dual channel).
- Progressive scan.
- Matrox Odyssey eCL/XCL receiving external trigger signal.
- Matrox Odyssey eCL/XCL sending EXPOSURE1 (CC1) signal to camera to initiate and control exposure time.
- Matrox Odyssey eCL/XCL receiving LDV, FDV, CLK and video signal from camera.
- DCF used: [4000mD2048x2048_10bit2TapAsync.DCF](#)



Specifics about the
interface modes

Camera Interface Details

Mode 1: Continuous

- Frame Rate:** Matrox Odyssey eCL/XCL receives the continuous video from the camera at 16 frames per second at full resolution.
- Exposure time:** Exposure time is determined by the shutter setting. Refer to the camera manual for more information.

Continued

Matrox Odyssey eCL/XCL

Camera Interface Application Note

ADIMEC 4000m/D

April 16, 2008

Specifics about the
interface modes

Camera Interface Details (cont.)

Mode 1: Continuous

- **Camera Control Software settings:** Use ONL's imCamControl() or imDigControl() function, MIL's MdigControl() function, Adimec's configuration tool or Windows HyperTerminal to set the camera controls as follows:

Control	Setting
10 bit Output	@OR10
Continuous Mode	@MO4

Mode 2: Pseudo-continuous

- **Frame Rate/Exposure time:** The frame rate is determined by the EXPOSURE1 (CC1) setting in the DCF. Changing the frequency (delay period) will control the frame rate, while changing the width (falling edge to rising edge) of EXPOSURE1 (CC1) controls the frame rate as well as exposure time. The frame rate and exposure time can be modified using Matrox Intellicam, with the ONL imCamControl() or imDigControl() function, or with the MIL MdigControl() function. Refer to the respective manual for more information.
- **Camera Control Software settings:** Use ONL's imCamControl() or imDigControl() function, MIL's MdigControl() function, Adimec's configuration tool or Windows HyperTerminal to set the camera controls as follows:

Control	Setting
10 bit Output	@OR10
Control Mode	@MO5
Exposure Polarity	@EP1

Mode 3: Asynchronous reset

- **Frame Rate:** The frame rate is determined by the frequency of the external trigger signal.
- **Exposure time:** The width (falling edge to rising edge) of the EXPOSURE1 (CC1) signal is the exposure time. The exposure time can be modified using Matrox Intellicam, ONL imCamControl() or imDigControl() function, or with the MIL MdigControl() function. Refer to the respective manual for more information.
- **Camera Control Software settings:** Same as Mode 2: Pseudo-continuous.

Matrox Odyssey eCL/XCL

Camera Interface Application Note

ADIMEC 4000m/D

April 16, 2008

Cabling details for the
interface modes

Cabling Requirements

Modes 1 and 2: Continuous and Pseudo-continuous

- **Cable and Connection:** Standard Camera Link cable.

Mode 3: Asynchronous reset

- **Cable and Connection:** Standard Camera Link.
- **External trigger:** External trigger should be connected to the OPTO TRIG input of the 9-pin connector (pins 7 and 2) on the Expanded I/O adapter bracket.

EXPANDED I/O BRACKET (9-pin connector)

External Trigger Source

OPTOTRIG +	07	←	SIGNAL	--
OPTOTRIG -	02	←	GROUND	--

The DCFs mentioned in this application note are also attached (embedded) to this PDF file – use the Adobe Reader's View File Attachment to access the DCF files. The information furnished by Matrox Electronics System, Ltd. is believed to be accurate and reliable. Please verify all interface connections with camera documentation or manual. Contact your local sales representative or Matrox Sales office or Matrox Imaging Applications at 514-822-6061 for assistance. © Matrox Electronic Systems Ltd, 2008-2011.

Matrox Electronic Systems Ltd.

1055 St. Regis Blvd.
Dorval, Quebec H9P 2T4
Canada
Tel: (514) 685-2630
Fax: (514) 822-6273

ODY-CID-073

