

DALSA CL-P1-1024W (PIRANHA)

May 28, 1999

Camera Descriptions	 1024 × 8-bit. Dual channel LVDS digital video. External synchronization required. Exposure control. Maximum data rate: 25 MHz per output. 								
Interface modes	Fixed line scan rate, variable line scan								
Camera Interface Briefs	Mode 1: Fixed line scan rate								
	 1024 × 8-bit. Dual channel LVDS digital video. DCF configured for 512 lines per virtual frame. Line scan rate is fixed and determined by the frequency of the EXPOSURE1 (EXSYNC) signal. Matrox Genesis sending EXPOSURE1 (EXSYNC) and EXPOSURE2 (PRIN) signals to camera; the EXPOSURE1 (EXSYNC) signal controls line readout and EXPOSURE2 (PRIN) signal controls exposure time. Matrox Genesis receiving PIXEL CLOCK (STROBE @ 25 MHz), HSYNC (LVAL) and video signals from camera; a high LVAL signal indicates valid pixels. DCF used: CLP1DEL2.DCF 								
	Mode 2: Variable line scan rate VIDEO PRIN EXSYNC STROBE LVAL VIDEO PRIN EXSYNC STROBE LVAL VAL VAL VAL VAL VAL VAL VA								

DALSA CL-P1-1024W (PIRANHA)

May 28, 1999

Camera	Mode 1: Fixed line scan rate mode							
Camera Interface Details	 Matrox Genesis sends the EXPOSURE1 (EXSYNC) signal to the camera; the camera awaits the rising edge of the signal and after a short (constant) delay initiates line readout. Line rate: The EXPOSURE2 (PRIN) period in the DCF specifies the line rate of the camera. The EXPOSURE2 (PRIN) period is currently set to 3110 pixels. With a 25 MHz pixel clock, this translates to an 8.0 kHz line rate. Virtual frame rate: The virtual frame rate for the current settings of the DCF is 15.7 Hz. Exposure time: The time between the rising edge of the EXPOSURE2 (PRIN) and EXPOSURE1 (EXSYNC) signals is the exposure time. The default exposure time for this DCF is 100 µs. In order to select the exposure time, the width and deployment time of EXPOSURE1 (EXSYNC) and EXPOSURE2 (PRIN) must be set in Matrox Intellicam. The exposure time of the camera can be modified in the DCF using Matrox Intellicam, Genesis Native Library function imCamControl() or with the MIL digitizer control function MdigControl(). Refer to the appropriate manual or user guide for additional 							
	information.							
	• Maximum / minimum exposure time: Since the Matrox Genesis timer is 16-bit wide, the maximum exposure time is calculated to be $65536/25$ MHz = 2.62 ms. For proper operation, the exposure signal must remain inactive for a minimum of 6 clock pulses before being asserted. Therefore the minimum exposure time is 240 ns.							
	• Smallest exposure time increment : The pixel clock is the reference clock that the exposure time is being set by. The smallest increment of the exposure time is 40 ns .							
	T2 = 124.4 ms							
	Exposure1 (EXSYNC)							
	HSYNC (LVAL) Delay Delay = 22.9 ms Video Valid = 20.5 ms							
	Mode 2 : Variable line scan rate							
	• Once it has received the external trigger signal, Matrox Genesis sends the EXPOSURE2 (PRIN) signal to the camera to initiate exposure. Matrox Genesis will send the EXPOSURE1 (EXSYNC) signal to the camera following a delay that is equal to the desired exposure time. A short (constant) delay will follow after receiving the EXPOSURE1 (EXSYNC), followed by the camera sending the HSYNC (LVAL) signal to the Matrox Genesis to initiate line readout.							

DALSA CL-P1-1024W (PIRANHA)

Camera Interface Details (continued)	 Line and virtual frame rate: Line and virtual frame rates are variable and controlled by the frequency of the external trigger signal. Maximum exposure time, Minimum exposure time, and Smallest exposure time increments: are the same as for Mode 1: <i>Fixed line scan rate</i> 							
	Mode 1: Fixed line scan rate							
Cabling								
Requirements	• DBHD100-TO-OPEN cable and GEN/DIG/BRD/L/_ board required for digital data, synchronization and control signals.							
	•							
	• Connections between the 37-pin connector (OS1/OS2) of the camera and the 100-pin connector of the GEN-DIG-BRD/L/_ are as follows:							
	DALSA CL	2-P1-1024W		GEN-DIG-BRD/L/_				
		nector – OS1/OS2)		(100-pin connector)				
	Pin name	Pin no.		Pin name	Pin no.			
	D0	16	\rightarrow	DATA, INPUT, 0+	01			
	D0B	35	\rightarrow	DATA, INPUT, 0-	02			
	D1	15	\rightarrow	DATA, INPUT, 1+	03			
	D1B	34	\rightarrow	DATA, INPUT, 1-	04			
	D2	14	\rightarrow	DATA, INPUT, 2+	05			
	D2B	33	\rightarrow	DATA, INPUT, 2-	06			
	D3	13	\rightarrow	DATA, INPUT, 3+	07			
	D3B	32	\rightarrow	DATA, INPUT, 3-	08			
	D4	12	\rightarrow	DATA, INPUT, 4+	09			
	D4B	31	\rightarrow	DATA, INPUT, 4-	10			
	D5	11	\rightarrow	DATA, INPUT, 5+	11			
	D5B	30	\rightarrow	DATA, INPUT, 5-	12			
	D6	10	\rightarrow	DATA, INPUT, 6+	13			
	D6B	29	\rightarrow	DATA, INPUT, 6-	13			
	D7	09	\rightarrow	DATA, INPUT, 7+	15			
	D7B	28	\rightarrow	DATA, INPUT, 7-	16			
	D0	08	\rightarrow	DATA, INPUT, 8+	10			
	DOB	27	\rightarrow	DATA, INPUT, 8-	18			
	D0B D1	07	\rightarrow	DATA, INPUT, 9+	18			
	D1B	26	\rightarrow	DATA, INPUT, 9-	20			
	D1B D2	20 06	\rightarrow	DATA, INPUT, 10+	20 21			
	D2 D2B	25	\rightarrow	DATA, INPUT, 10+	21 22			
	D2B D3	05	\rightarrow	DATA, INPUT, 11+	22			
	D3 D3B	24	\rightarrow	DATA, INPUT, 11+ DATA, INPUT, 11-	23 24			
	D3B D4	04	\rightarrow	DATA, INPUT, 11- DATA, INPUT, 12+	24 25			
	D4 D4B	23	\rightarrow	DATA, INPUT, 12+ DATA, INPUT, 12-	23 26			
	D4B D5	03	\rightarrow	DATA, INPUT, 12- DATA, INPUT, 13+	20 27			
	D5 D5B	22	\rightarrow	DATA, INPUT, 13+ DATA, INPUT, 13-	27 28			
	D5B D6	02	\rightarrow		28 29			
			\rightarrow	DATA, INPUT, 14+				
	D6B	21	\rightarrow	DATA, INPUT, 14-	30			
	D7	01	\rightarrow	DATA, INPUT, 15+	31			
	D7B	20		DATA, INPUT, 15-	32			
	continued							

May 28, 1999

G E N E S I S

DALSA CL-P1-1024W (PIRANHA)

May 28, 1999

Cabling Requirements (continued)	DALSA CL-I (37-pin conne STROBE STROBEB LVAL LVAL LVALB	ector – OS1/OS2) 17	$\begin{array}{c} \rightarrow \\ \rightarrow \\ \rightarrow \\ \rightarrow \\ \rightarrow \end{array}$	GEN-DIG-BRD/L/_ (100-pin connector) CLOCK, INPUT, + CLOCK, INPUT, - HSYNC, INPUT, + HSYNC, INPUT, -	39 40 33 34				
	• Connections between the 15-pin female connector (Control) of the camera and the 100-pin connector on the GEN-DIG-BRD/L/_ are as follows:								
	DALSA CL-P1-1024W (15-pin connector – Control)			GEN-DIG-BRD/L/_ (100-pin connector)					
	Pin name	Pin no.		Pin name	Pin no.				
	EXSYNC	12	\leftarrow	EXPOSURE1, OUTPUT, +	95				
	EXSYNCB	04	\leftarrow	EXPOSURE1, OUTPUT, -	96				
	PRIN	05	\leftarrow	EXPOSURE2, OUTPUT, +	97				
	PRINB	13	\leftarrow	EXPOSURE2, OUTPUT, -	98				
	 Connections between the 15-pin male power connector of the camera and the power supply are as described in the DALSA camera manual. Mode 2: Variable line scan rate DBHD100-TO-OPEN and IMG-7W2-TO-5BNC cables, and GEN/DIG/BRD/L/_ board required for TTL external trigger, digital data, synchronization and control signals. TTL external trigger source should be connected to the TTL trigger input of IMG-7W2-TO-5BNC cable. All other connections are as in Mode 1: <i>Fixed line scan rate</i> 								

The DCF(s) mentioned in this application note can be found on the MIL and Native Library CD, or our FTP site (ftp.matrox.com). The information furnished by Matrox Electronics System, Ltd. is believed to be accurate and reliable. Please verify all interface connections with camera documentation or manual. Contact your local sales representative or Matrox Sales office or Matrox Imaging Applications at 514-822-6061 for assistance.

Corporate Headquarters: Canada and U.S.A. Matrox Electronic Systems Ltd. 1055 St.Regis Blvd. Dorval, Quebec, Canada H9P 2T4 Tel: (514) 685-7230 Fax: (514) 822-6273

