

Application Note:

Interfacing non-standard cameras to Matrox Genesis

DVC 1310

October 5, 2000

Camera Descriptions	• 1300 × 1030/515 × 10-bit @ 12/24 fps. • Single channel RS-422/LVDS digital video output. • Progressive scan. • External synchronization. • Pixel clock rate: 20.25 MHz.												
Interface mode	• Pseudo-continuous												
Camera Interface Briefs	Mode: Pseudo-continuous (normal mode)  *Matrox Genesis main board with grab module **Matrox RS-422 or LVDS digital data input board • 1300 × 1030/515 × 10-bit @ 12/24 fps. • Single channel RS-422/LVDS digital video. • Progressive scan. • Continuous video. • Matrox Genesis receiving HSYNC (ENL), VSYNC (ENF), PIXEL CLOCK (PIXCLK @ 20.25 MHz) and video signals from camera. • DCF used: G1310C12.DCF (1300 × 1030 × 10-bit @ 12 fps) • DCF used: G1310C24.DCF (1300 × 515 × 10-bit @ 24 fps)												
Camera Interface Details	Mode: Pseudo-continuous (normal mode) • Frame rate: Pseudo-continuous and fixed (12 or 24 fps), frame rate is inversely proportionate to the exposure time. • Exposure time: For this camera mode (normal), exposure time is fixed and inversely proportionate to the frame rate. Refer to the camera manual for more information. • Camera switch settings: Refer to the camera manual for additional information. Internal switches for this mode should be set as follows: <table><tr><th>Setting/DCF</th><th>G1310C12.DCF</th><th>G1310C24.DCF</th></tr><tr><td>DB (8:1)</td><td>Disabled</td><td>Disabled</td></tr><tr><td>EXT</td><td>1</td><td>0</td></tr><tr><td>MC (2:0)</td><td>111</td><td>111</td></tr></table>	Setting/DCF	G1310C12.DCF	G1310C24.DCF	DB (8:1)	Disabled	Disabled	EXT	1	0	MC (2:0)	111	111
Setting/DCF	G1310C12.DCF	G1310C24.DCF											
DB (8:1)	Disabled	Disabled											
EXT	1	0											
MC (2:0)	111	111											

Application Note:

Interfacing non-standard cameras to Matrox Genesis

DVC 1310

October 5, 2000

Cabling Requirements

Mode: Pseudo-continuous (normal mode)

- DBHD100-TO-OPEN cable and GEN/DIG/BRD/R/_ or GEN/DIG/BRD/L/_ board required for synchronization, control and video signals from camera.
- Connections should be made between the 44-pin connector (**DIGITAL VIDEO**) of the camera and Matrox Genesis are as follows:

GEN/DIG/BRD/_/_ (100-pin connector)

Pin name

Pin no.

CLOCK, INPUT, -	40
CLOCK, INPUT, +	39
GROUND	37
GROUND	38
DATA, INPUT, 9-	20
DATA, INPUT, 9+	19
EXPOSURE1, OUTPUT+	95
DATA, INPUT, 8-	18
DATA, INPUT, 8+	17
EXPOSURE1, OUTPUT-	96
DATA, INPUT, 7-	16
DATA, INPUT, 7+	15
CAM CTRL BIT2, OUTPUT, TTL	100
DATA, INPUT, 6-	14
DATA, INPUT, 6+	13
CAM CTRL BIT1, OUTPUT, TTL	99
DATA, INPUT, 5-	12
DATA, INPUT, 5+	11
CAM CTRL BIT0, OUTPUT, TTL	49
DATA, INPUT, 4-	10
DATA, INPUT, 4+	09
EXPOSURE1, OUTPUT, TTL*	87*
DATA, INPUT, 3-	08
DATA, INPUT, 3+	07
DATA, INPUT, 2-	06
DATA, INPUT, 2+	05
GROUND	37
DATA, INPUT, 1-	04
DATA, INPUT, 1+	03
DATA, INPUT, 0-	02
DATA, INPUT, 0+	01

DVC 1310

(44-pin connector)

Pin name

Pin no.

← PIXCLK-	16
← PIXCLK+	01
← GND	17
← GND	02
← D9- (MSB)	19
← D9+ (MSB)	04
→ INOUT1+	34
← D8-	20
← D8+	05
→ INOUT1-	35
← D7-	21
← D7+	06
→ MC2	36
← D6-	22
← D6+	07
→ MC1	37
← D5-	23
← D5+	08
→ MC0	38
← D4-	24
← D4+	09
→ VRST_INT*	39*
← D3-	25
← D3+	10
← D2-	26
← D2+	11
-- GND	41
← D1-	27
← D1+	12
← D0- (LSB)	28
← D0+ (LSB)	13

* This connection is not required for this mode, however allows this cable to be used with other modes.

continued

Application Note:

Interfacing non-standard cameras to Matrox Genesis

DVC 1310

October 5, 2000

Cabling Requirements	GEN/DIG/BRD/_/_ (100-pin connector)		DVC 1310 (44-pin connector)	
	Pin name	Pin no.	Pin name	Pin no.
	GROUND	38	-- GND	43
	VSYNC, INPUT -	36	← ENF-	29
	VSYNC, INPUT +	35	← ENF+	14
	HSYNC, INPUT -	34	← ENL-	30
	HSYNC, INPUT +	33	← ENL+	15

The DCF(s) mentioned in this application note can be found on the MIL and Native Library CD, or our FTP site ([ftp.matrox.com](ftp:ftp.matrox.com)). The information furnished by Matrox Electronics System, Ltd. is believed to be accurate and reliable. Please verify all interface connections with camera documentation or manual. Contact your local sales representative or Matrox Sales office or Matrox Imaging Applications at 514-822-6061 for assistance.

Corporate headquarters:

Canada and U.S.A.

Matrox Electronic Systems Ltd.
1055 St. Regis Blvd.
Dorval, Quebec H9P 2T4
Canada
Tel: (514) 685-2630
Fax: (514) 822-6273

